



Pre Plumbed Cylinder

For use with Altherma Monobloc System

UK.PPC

Pre Plumbed Cylinder

Daikin UK's new Pre Plumbed Cylinder is the perfect partner to the Daikin Altherma Monobloc system, offering plug & play installation with all key hydraulics included to ensure a fast and easy installation. This slimline model has a small footprint to minimise the floor space required, making it ideal for smaller properties. Yet it delivers maximum performance, thanks to a built-in 20 litre buffer vessel and pre-fitted magnetic filter to ensure optimal performance of the Daikin Altherma Monobloc.

The Pre Plumbed Cylinder comes pre-fitted with:

- > 20 litre buffer vessel
- > G3 kit (expansion vessel supplied loose)
- > Monobloc wiring centre
- > ESBE 3-way valve
- > Magnetic filter
- > Automatic air vents
- > Dual immersion heaters
- > Thermostatic mixing valve



Pre Plumbed Cylinder

Pre-plumbed Cylinder



Domestic hot water cylinder			UK.PPC150	UK.PPC180	UK.PPC210	2
Description			150l pre-plumbed cylinder	180l pre-plumbed cylinder	210l pre-plumbed cylinder	
Suitable for			Daikin Altherma R410a Monobloc			
Energy efficiency class			B	B	C	C
Standing heat loss (ErP)	W		54	58	63	88
Storage volume	L		148	179	209	248
Standing heat loss	kWh/24h		1.29	1.39	1.50	2.10
Max water temperature	°C		90			
Primary immersion heater capacity	kW		3			
Primary immersion heater power supply			1-phase / 230V / 50Hz			
Primary immersion heater recommended fuses	A		16			
Secondary immersion heater capacity	kW		3			
Secondary immersion heater power supply			1-phase / 230V / 50Hz			
Secondary immersion heater recommended fuses	A		16			
Height	mm		1550	1676	1864	2164
Diameter	mm		550	550	550	600
Empty weight	kg		46	56	59	71
Material inside cylinder			Stainless steel 2304			
Piping connections (diameter)	Water inlet H/E	mm	28			
	Water outlet H/E	mm	28			
	Cold water in	mm	22			
	Hot water out	mm	22			

Domestic hot water cylinder			UK.PPC150SL	UK.PPC180SL
Description			150l slimline pre-plumbed cylinder	180l slimline pre-plumbed cylinder
Suitable for			Daikin Altherma R410a Monobloc	
Energy efficiency class			B	B
Standing heat loss (ErP)	W		52	58
Storage volume	L		152	178
Standing heat loss	kWh/24h		1.23	1.39
Max water temperature	°C		90	
Primary immersion heater capacity	kW		3	
Primary immersion heater power supply			1-phase / 230V / 50Hz	
Primary immersion heater recommended fuses	A		16	
Secondary immersion heater capacity	kW		3	
Secondary immersion heater power supply			1-phase / 230V / 50Hz	
Secondary immersion heater recommended fuses	A		16	
Height	mm		1869	2085
Diameter	mm		475	475
Empty weight	kg		59	67
Material inside cylinder			Stainless steel 2304	
Piping connections (diameter)	Water inlet H/E	inch	28	
	Water outlet H/E	inch	28	
	Cold water in	inch	22	
	Hot water out	inch	22	

Features:

- > The perfect partner to the Daikin Altherma Monobloc
- > Plug & play installation, all key hydraulics included to ensure a fast and easy installation
- > Optimising floor space, the slimline model has a small footprint, making it ideal for smaller properties
- > Maximum performance, built-in 20 litre buffer vessel and pre-fitted magnetic filter to ensure the best performance of the Daikin Altherma Monobloc
- > Pre-fitted with 20 litre buffer vessel, G3 kit (expansion vessel supplied loose), Monobloc wiring centre, ESBE 3-way valve, Magnetic filter, Automatic air vents, Dual immersion heaters and thermostatic mixing valve

The present leaflet is drawn up by way of information only and does not constitute an offer binding upon Daikin UK. Daikin UK has compiled the content of this leaflet to the best of its knowledge. No express or implied warranty is given for the completeness, accuracy, reliability or fitness for particular purpose of its content and the products and services presented therein. Specifications are subject to change without prior notice. Daikin UK explicitly rejects any liability for any direct or indirect damage, in the broadest sense, arising from or related to the use and/or interpretation of this leaflet. All content is copyrighted by Daikin UK.



Daikin Europe N.V. participates in the Eurovent Certification programme for Air conditioners (AC), Liquid Chilling Packages (LCP), Air handling units (AHU) and Fan coil units (FCU). Check ongoing validity of certificate online: www.eurovent-certification.com or using: www.certiflash.com

